

DOSADOR MULTIFUNCIONAL– MODELO B-A6

The B-A6 has a bright four-digit LED screen and automatically cycle, suitable to dispense for mass production or for the products which are required high precision.

Dispensing timed micro adjust from 0.01 to 0-99.99 seconds. The unit can either be controlled with a foot pedal or a finger switch for hand-held dispensing applications.



SPECIFICATIONS

1. Power:	AC220V \pm 10% 50HZ AC110V \pm 10% 60HZ, 12W
2. Air Input:	Max. 0.99Mpa
3. Air Output:	0.05Mpa - 0.99Mpa
4. Dispensing Time:	0.01 – 99.99s
5. Dispensing Modes:	Manual and with a total of 16 combinations
5. Timing Intervals:	0.1 – 9.9s
7. Suck-back Feature:	adjust vacuum control to 600 mmHg
8. Repeat Tolerance:	\pm 0.01%
9. Dispensing Frequency:	>1000times/min
10. Minimum dispensing:	0.0001ml
11. Dimension:	235mm x 225mm x 63mm
12. Weight:	3kg

Ítems de consumo sugeridos:



ISAURA Rodrigues

SURPASS – MATERIAL & TECHNOLOGY LTDA

surpass@surpass-smt.com.br fones: (11) 3042 0705 019-93950587 / 011-97576 1602